



## Zhejiang Huaxin bearing accessories C...



PLB6935R Bearing 2D drawings and 3D CAD models

2.188 Inch | 55.575 Millimeter x 0 Inch | 0  
 Millimeter x 3.5 Inch | 88.9 Millimeter LINK BELT  
 PLB6935R Pillow Block Bearings

Bearing No. PLB6935R

|                           |  |
|---------------------------|--|
| Category                  | Pillow Block Bearings  |
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 18.614   |
| EAN                       | 0662327118389  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Adapter Sleeve   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22313LBC3  |
| Seals                     | Multi Labyrinth  |
| Housing Configuration     | 2 Piece Split  |
| Inch - Metric             | Inch   |
| Other Features            | Double Row   |
| Long Description          | 2 Bolt Pillow Block; 2-3/16" Bore; 3-1/2" Base to Center Height; Adapter Sleeve Mount; Spherical Roller Bearing; 9-5/8" Minimum Bolt Spacing; 11" Bolt |



## Zhejiang Huaxin bearing accessories C...

|                               |   |
|-------------------------------|---|
|                               | Spacing Maximum;<br>Relubricatab                            |
| Category                      | Pillow Block  |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer URL              | <a href="http://www.rexnord.com">http://www.rexnord.com</a> |
| Manufacturer Item Number      | PLB6935R  |
| Manufacturer Internal Number  | 5811838   |
| Weight / LBS                  | 41  |
| D                             | 0 Inch   0 Millimeter                                       |
| Actual Bolt Center to Center  | 0 Inch   0 Millimeter                                       |
| Bolt Spacing Maximum          | 11 Inch   279.4 Millimeter                                  |
| d                             | 2.188 Inch   55.575 Millimeter                              |
| B                             | 3.5 Inch   88.9 Millimeter                                  |
| Nominal Bolt Center to Center | 10.3 Inch   260.5 Millimeter                                |
| Bolt Spacing Minimum          | 9.625 Inch   244.475 Millimeter                             |